

Pinnacle Stone Impregnator

CLASSIFICATION:

- Water-Based Stone Impregnator

910986-01

SCOPE:

FOR PROFESSIONAL USE ONLY *Pinnacle Stone Impregnator* is a high quality water- and oil-repellent product for use on all natural stone surfaces.

FEATURES AND BENEFITS:

Feature	Benefit
▪ Use on all types of natural stone, as well as terra-cotta, brick and terrazzo	▪ Facilitates long-term maintenance by increasing resistance to oil and water stains
▪ Not a topical sealer, actually penetrates and protects stone from within	▪ Allows the stone to “breathe” naturally, retaining almost all original permeability
▪ Provides protection from “rising damp”	▪ Helps prevent damage from moisture
▪ UV-resistant	▪ Interior or exterior use
▪ Invisible protection	▪ No color change on most treated surfaces

Approximate Coverage: Up to 1,200 ft²/gallon

(Actual coverage rate may vary depending on application, technique and surface condition)

DIRECTIONS FOR USE:

The area to be impregnated with *Pinnacle Stone Impregnator* should be totally dry and free of any topical coatings or soil. Apply *Pinnacle Stone Impregnator* using a roller, brush or sprayer. Allow 15 minutes for penetration. Remove any excess material with a dry absorbent cloth. On porous surfaces, a second application may be necessary. Allow 2 hours between coats for partial cure time. Area may be opened to foot traffic after 4 hours. Wait 24 hours before cleaning to allow for maximum protection. Allow newly installed floors 7 to 10 days to completely cure prior to impregnating. Over-usage on very porous surfaces may cause slight tonal change. Always test on an inconspicuous area prior to general use.

CHEMICAL PROPERTIES:

• Active Ingredients:	Name	CAS number	% by weight
	2-butoxyethanol	111-76-2	4
	Dipropyleneglycol monomethyl ether	34590-94-8	4
• pH (100%)	10.5		
• Specific Gravity	0.995		
• Initial Boiling Point	>100 °C		
• Solubility in Water	Easily soluble in cold water, hot water		

PHYSICAL PROPERTIES:

• Color	Opaque white
• State	Liquid
• Fragrance	Alcohol - like

ENVIRONMENT & SAFETY:

• Hazard Rating	Health - 1	Fire - 2	Reactivity - 0
-----------------	------------	----------	----------------

PRECAUTIONARY STATEMENTS:

Provide adequate ventilation. Protective gloves, safety glasses or goggles, overall/apron should be worn. Always wear appropriate personal protective clothing when using chemicals

FIRST AID:

Eye contact: Immediately flush eyes with running water for at least 15 minutes and seek medical attention of an eye physician. Skin contact: Remove contaminated clothing. Immediately wash exposed area thoroughly with water. If irritation persists, seek medical attention. Inhalation: Remove victim from exposure. If irritation persists, seek medical attention. Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed seek medical attention immediately.

FOR EMERGENCY MEDICAL INFORMATION IN USA OR CANADA, CALL 1-800-328-0026.

FOR EMERGENCY MEDICAL INFORMATION WORLDWIDE, CALL 1-651-222-5352 (USA).

READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.

PACKAGING & PRODUCT NUMBERS:

Size Available	Product Number
4/1-qt.	6277 1113

PROFESSIONAL PRODUCTS DIVISION

Ecolab Inc., 370 Wabasha Street, St. Paul, MN 55102 U.S.A.

5105 Tomken Road, Mississauga, Ont. Canada L4W2X5

www.ecolab.com 1-800-332-6522 © 2005 Ecolab Inc Printed in U.S.A. 0505

