

Material Safety Data Sheet



STONEMEDIC MPC MARBLE POLISHING COMPOUND

Section 1. Chemical product and company identification

Trade name : STONEMEDIC MPC MARBLE POLISHING COMPOUND
Product use : Floor care product
Supplier : Ecolab Inc. Professional Products Division
370 N. Wabasha St.
St. Paul, MN 55102
1-800-247-5362
Code : 911095
Date of issue : 21-October-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
alumina	1344-28-1	15
potassium hydrogen oxalate	127-95-7	>50

Section 3. Hazards identification

Physical state : Liquid. (paste)
Emergency overview : WARNING!

HARMFUL IF SWALLOWED.

CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Irritating to eyes.
Skin : Harmful in contact with skin. Irritating to skin.
Inhalation : Irritating to respiratory system.
Ingestion : Harmful if swallowed.
See toxicological Information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

Skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion : Rinse mouth; then drink one or two large glasses of water. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

Flash point : > 100°C
Fire fighting media and instructions : Use an extinguishing agent suitable for surrounding fires.

Dike area of fire to prevent product run-off.
 No specific hazard.

Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

Handling : Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.

Storage : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
 Do not store below -5°C

Section 8. Exposure Controls, Personal Protection

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

Eyes : Use safety eyewear designed to protect against splash of liquids.

Hands : Use chemical resistant, impervious gloves.

Skin : No protective equipment is needed under normal use conditions.

Respiratory : Avoid breathing vapor or mist.

Name

alumina

Exposure limits

ACGIH TLV (United States, 1/2004).

TWA: 10 mg/m³ 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

ACGIH TLV (United States, 1/2004).

TWA: 5 mg/m³ 8 hour(s). Form: Fume

Section 9. Physical and chemical properties

Physical state : Liquid. (paste)

Color : Amber.

Odor : citrus

pH : 1.25 (100%)

Boiling/condensation point : >100 °C

Specific gravity : 1.6 (Water = 1)

Solubility : Partially soluble in cold water, hot water.

Section 10. Stability and reactivity

- Stability** : The product is stable.
- Reactivity** : Reactive with metals, acids, alkalis.
Slightly reactive to reactive with organic materials.

Section 11. Toxicological information

Potential acute health effects

- Eyes** : Irritating to eyes.
- Skin** : Harmful in contact with skin. Irritating to skin.
- Inhalation** : Irritating to respiratory system.
- Ingestion** : Harmful if swallowed.
- Chronic effects on humans** : Contains material which causes damage to the following organs: kidneys, lungs, the nervous system, heart, upper respiratory tract, skin, eye, lens or cornea.

Section 12. Ecological information

- Products of degradation** : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ ...). Some metallic oxides.

Section 13. Disposal considerations

- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

- Waste classification** : Unused product is D002 (Corrosive)

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	UN2811	Toxic solids, organic, n.o.s.(Potassium binoxalate)	6.1	III	Limited quantity Yes. Special provisions IB8, IP3

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

- HCS Classification** : Irritating material
Target organ effects
- U.S. Federal regulations** : SARA 302/304/311/312 extremely hazardous substances: None.
SARA 302/304 emergency planning and notification: None.
- TSCA 8(b) inventory** : All materials are listed or exempt.
- SARA 313** : **Product name** **Concentration**
- Form R - Reporting requirements:** alumina 7.4927 - 22.478
- California prop. 65** : No products were found.

Section 16. Other information

Hazardous Material Information System (U.S.A.)	:	Health	*	2
		Fire hazard		0
		Reactivity		0
		Personal protection		B

Date of issue : 21-October-2005.

Responsible name : Regulatory Affairs

Date of previous issue : 25-March-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.